

738

DIGITAL

ABBE REFRACTOMETER

SALIENT FEATURE

- Stepping Motor means Accurate, reliable operation
- Direct readout of all measurement parameters
- Auto Range Showing
- Time Function for measurement
- Sound alarm at under 20% Torque
- Linear calibration
- Wide range power supply: 100V-240V

TECHNICAL SPECIFICATION

| | |
|------------------------------|---|
| MEASURING MODES | : 1.Refractive Index 2.Brix of sugar solution 3.Brix TC of sugar solution 4.Automatic detect Temp.shown in display |
| MEASUREMENT RANGE | : nD1.30000-1.70000 Brix:0-100% |
| MEASURING ACCURACY | : nD \pm 0.0002 Brix \pm 0.1% |
| MEASURING RESOLUTION | : (nD) \pm 0.0001 |
| TEMPERATURE RANGE(Min.0.1°C) | : 0-50°C |
| WEIGHT(GROSS) | : 12Kg |
| OVERALL DIMENSIONS | : 370mm x 240mm x 470mm |



STANDARD ACCESSORIES

| | |
|----------------------------|-------------------|
| Ascending and falling rack | 1 set |
| Protective frame of rotor | 1 No. |
| Rotors | (No.1,2,3,4 each) |
| Power adapter | 1 No. |
| Screw driver | 1 No. |
| Socket | 1 set |



Laboholic



CE FDA