






INTRODUCING

# MERA PAL UREA



-  • Wide Urea Range of 0-55% with accuracy of 0.3%
-  • Extremely water resistant (IP65)  
• Can be washed under running water
-  • Automatic Temperature Compensation (ATC)
-  • Measurement temperature direct display in °C
-  • Revolutionary new External Light interference (ELI) feature **Patented**



**Measurement Method**



1 Apply 2-3 drops on the prism surface.



2 Press the START key.



3 Measurement value and prism temperature are displayed in 3 seconds

**Digital Handheld Pocket Refractometer MERA PAL UREA specifications**

Cat.#	4694
Measurement range	0.0 to 55.0% UREA (Automatic Temperature Compensation) 10.0 to 40 °C
Resolution	0.1% UREA / 0.1 °C
Accuracy	± 0.3% UREA / 0.1 °C
Automatic temperature compensation range	10 to 40°C
Ambient temperature range	10 to 40°C
Battery life	Approx. 11,000 measurements (when using alkaline batteries)
Dimensions and weight	55(W)x31(D)x109(H)mm, 100g (Main unit only)

All ATAGO products are designed and manufactured in Japan.

**HACCP GMP GLP**

ATAGO products comply with HACCP, GMP, and GLP system standards.

**ATAGO CO., LTD.**

Headquarters: The Front Tower Shiba Koen, 23rd Floor  
2-6-3 Shiba-koen, Minato-ku, Tokyo 105-0011, Japan  
TEL : 81-3-3431-1943 FAX : 81-3-3431-1945  
overseas@atago.net http://www.atago.net/



\* Specifications and appearance are subject to change without notice.

**ATAGO INDIA Instruments Pvt. Ltd.**

Unit # 103, Western Edge II, Opp. Magathane Bus Depot,  
Off. Western Express Highway, Borivali (East), MUMBAI – 400 066  
customerservice@atago-india.com, Tel : 022-4071 3232

NEW DELHI - customerservice-del@atago-india.com, Tel : 011-2205 0093  
CHENNAI - customerservice-chn@atago-india.com, Tel. : 044-4042 3171  
BENGALURU - customerservice-blr@atago-india.com  
HYDERABAD - customerservice-hyd@atago-india.com  
AHMEDABAD - customerservice-ahd@atago-india.com

