

PORTABLE INSTRUMENTS

14/17/19/28



SPECIFICATIONS

| MODEL NO. | LH-14 | LH-17 | LH-19 | LH-28 |
|--------------------|--------------------------|----------------------------|-------------------------|-----------------------|
| RANGE | 0 - 14 pH | 0-1999 μ S, 0-19.99 mS | 0-1999 ppm, 0-19.99 ppt | 0 – 19.9 ppm |
| RESOLUTION | 0.01 pH | 1 μ S | 1 ppm | 0.1 ppm |
| IMPEDANCE | > 10 ¹² ohms | - | - | - |
| SENSOR | Combination pH Electrode | Cond. Cell (Dip type) | TDS Cell (Dip type) | Amperometric DO Probe |
| BATTERY | 9V DC | 9V DC | 9V DC | 9V DC |
| ACCURACY | 0.01pH | \pm 1% FS | \pm 1% FS | \pm 2% FS |
| TEMP. COMP. | 0 - 100°C (Manual) | - | - | 5 to 55°C |
| DISPLAY | 3½ digit LCD | 3½ digit LCD | 3½ digit LCD | 3½ digit LCD |
| SIZE | 180 x 85 x 30 mm | 180 x 85 x 30 mm | 180 x 85 x 30 mm | 180 x 85 x 30 mm |
| WEIGHT | 250 gm. (Approx) | 250 gm. (Approx.) | 250 gm. (Approx.) | 250 gm. (Approx.) |