

GLOLAB

I N S T R U M E N T S

Leak Test Apparatus - GVLT-201



FEATURES

1. Automatic pressure Correction
2. Self-Test, Graphical Display
3. High Quality Pumps/Relays
4. Quick Fit PU Tubing
5. Data transfer to PC through LAN/RS 232 port/USB
6. Printer interface
7. 3 level Password

TECHNICAL SPECIFICATION

Vacuum Range	: 150 - 600 mmHg
Pressure Unit	: mmHg / Psi / kPa
Accuracy	: ± 10 mmHg
Display	: 128 x 64 Monochrome Graphic Display
Keypad	: Alphanumeric Keypad
Interface Port	: LAN, RS-232, External 80/40 column Printer and Printer interface
Hold Time	: Up to 30 Minutes
Batch Test Results	: 20 Test and 10 Methods with Date and Time Available
Accessories	: Polycarbonate Desiccator along with connecting tube, Instruction Manual
Password Protection	: 3 Tere Password Protection
Balance Interface	: At Extra cost (Optional)
Dimensions [L X B X H]	: 360 X 260 X 170 mm
Weight	: 25.5lbs / 11.6 kg
Electrical Power	: 230V \pm 23V, 50/60 Hz or 115V \pm 15V, 50/60 Hz