





RM-03 Pro

Salient Features for RM-03 Pro:

- 9 Memory programs
- Safety lid lock to prevent running unless lid is closed
- LCD display of parameters
- BLDC Motor
- Supplied with 2 Rotors

Rotors for RM-03 Pro						
 Micro Tube Rotor Max speed RPM 14500 Max RCF (g) 14104				 4 Strips PCR Rotor Max. Speed RPM 14500 Max RCF (g) 12576		
Image of Tube				Image of Tube		
Tube Capacity (ml)	2	0.5	0.2	Tube Capacity (ml)	4 Strips of 8 x 0.2	
Type of Tube	Micro	Micro	Micro	Type of Tube	PCR	
Insert Supplied	No	Yes	Yes	No of tubes/rotor	4	
No of tubes/Insert	-	1	1	Ø x L (mm)	6 x 78	
No of tubes/rotor	12	12	12	Tubes supplied	No	
Ø x L (mm)	11 x 41	7.5 x 31	6 x 22			
Tubes supplied	No	No	No			

(Rotor supplied with all suitable inserts)


Technical Data	
Model	RM-03 Pro
Max Speed	14500rpm
Max. RCF	14100g
Rotor Supplied	Micro tube rotor, PCR strip rotor
Timer range	30secs-59min
No. of Programs	9
Dimension (WxDxH) (mm)	180x270x105

Supply: 220-240 Volts, 50 Hz Single Phase.

Mini Centrifuge

Salient Features for RM-02 Pro

- Higher Speed upto 7000 RPM
- Multi-rotor, more working capacity
- Low Centre of gravity for stable operation
- High frequency and wide voltage
- Low noise
- Supplied with Hybrid Rotor-accomodates microtubes & PCR Strips

Rotor for RM-02 Pro				
 Micro Hybrid Rotor Max speed RPM 7000 Max RCF (g) 3286				
Image of Tube				
Tube Capacity (ml)	2 / 1.5	0.5	0.2	4 Strips of 8 x 0.2
Type of Tube	Micro	Micro	Micro	PCR
Insert Supplied	No	Yes	Yes	No
No of tubes/Insert	-	1	1	-
No of tubes/rotor	12	12	12	4
Ø x L (mm)	11 x 41	7.5 x 31	6 x 22	6 x 78
Tubes supplied	No	No	No	No

(Rotor supplied with all suitable inserts)



RM-02 Pro

Technical Data	
Model	RM-02 Pro
Control Mode	Digital Display & Button
Max Speed	7000rpm
Max RCF	3280xg
Timer range	10sec-99min
Dimension (WxDxH) (mm)	180x185x135

Supply: 220-240 Volts, 50 Hz Single Phase.