

B-ONE PLUS VISCOMETER

MADE IN FRANCE



Your Solutions to Sticky Problems!

VISCOMETER RHEOMETER TEXTURE



The Prime Solution to Sticky Problems!

Most versatile, Most affordable with Power Packed Features!

The ONLY Touch Screen Viscometer in its class to offer continuous sensing & data display

- 7" Touch Screen Display
- Wide Speed Range upto 250rpm
- Rotating Spring Less Technology
- Robust Ball Bearing Suspension
- SS316 Spindles
- Bayonet Fitting for Quick & EZ Spindle Connection
- Direct measure with Time to Stop
- Built-in USER Mode & LOCK Mode
- Built-in USB Port for Data Transfer
- Units: cP (Centipoise), mPa.s/Pa.s(Poise)
- Accuracy: 1% of Full-Scale Range
- Readability: +/- 0.2%
- Displays: Viscosity, Speed, Torque(%), Shear Stress, Shear Rate, Time, Temperature (Optional probe required)
- Auto Range (Min. & Max. Viscosity) (Range depends on speed & spindle selected)



- Two Viscometer Range!
 - LV & RV in 1 Viscometer (LR)
 - RV, HA - 5HB in 1 Viscometer (HR)
- Exactly same matching comparing results

+ OPTIONALS

- Additional Spindle Set (LV or RV)
- Viscosity Standards
- Ultra Low Viscosity Measurement Package
- Small Volume Sample Measurement Package
- HeliPro Stand with T-bar Spindles
- High Temp. Viscosity Measurement Thermocell Package
- DIN Measuring System
- Vane Spindles
- KU1-10 KREBS Spindle
- Temperature Control System
- Barcode Scanner
- Screen Protector
- Carrying Case
- LAMiCare Extended Warranty* (Includes Parts, Labor & Services; warranty against manufacturing defects)
- Annual Instrument Calibration & Certification

WHAT'S INCLUDED?

- Main Viscometer with Ball Bearing Suspension
- Calibration Certificate
- RTD Temp. Sensing Probe (-50 to 300°C)
- Bayonet Coupling System (Quick Connect & EZ Spindle Lock)
- SS316 - 6 spindles (RV/HA/HB) or SS316 - 4 spindles (LV)
- Viscometer Stand with stop ring
- AC Adapter with power cable
- Operational Manual
- Touch Pen
- Screen Cleaning Cloth

Model	VISCOSITY RANGE		Accuracy	Readability	SPEEDS	No. of Speeds
	Min.	Max.				
B-ONE PLUS LR (Low Range LV-RV)	1*	23M	1% of FSR	+/-0.2%	0.1-250 RPM	UNLIMITED
B-ONE PLUS HR (High Range RV, HA-5HB)	9*	377M*	1% of FSR	+/-0.2%	0.1-250 RPM	UNLIMITED

Dimensions: L180xW135xH250mm, 6.7kg. Stand: L280xW200xH30mm, SS Rod 500mm.
 *Minimum range can be extended to as low as 1cP (LR)/9cP (HR) with the use of MS-ULV/MS-SV Adapter
 *Maximum range can be extended to as high as 377M cP with use of special spindle
 M = 1 million | cP = Centipoise | mPa.s = Millipascal Seconds |
 FSR = Full Scale Range viscosity measured with Spindle/Speed combination

Customer Partner



LAMI INDIA (For Sales-Support-Service in India)
 L1, First International Financial Center
 Plot No.C54/C55, G Block, BKC
 Bandra East, Mumbai - 400 051 India

+91 (22) 6864 3982
www.lamiindia.com
sales@lamiindia.com