



Portable Turbidity Meter LH-340

MODEL	LH-340
Type	Portable
Description	High-precision Turbidity
Minimum readout (NTU)	0.001
Measuring range (NTU)	0-10
	0-100
	0-1000
	0-4000
Basic error	±3%FS
Repeatability	≤0.5%
Zero drift	±0.5%FS
Applications	Factory condensate water, Domestic sewage
Power	Lithium battery 3.7v/5200mA
Output	Micro USB
Dimensions /N.W.	210x105x65mm/500g
SHIPPING SIZE /G.W.	300x240x90mm/1 kg
STANDARD ACCESSORIES	Cuvette cup x 2 pc
	Charger
	Suitcase
	Manual

SALIENT FEATURES

- ✓ 4.3 inch coloured TFT screen with friendly UI.
- ✓ Contain 200 curves and customize high precision test curve according to measurement ranges. Users can set up different piecewise curve and coefficient subject to different concentrations which will literally improve measurement precision.
- ✓ ARM9 main control chip makes operations easy, response quick and big storage up to 500M.
- ✓ Adopt special and high precision light filter system to ensure the instruments' stability and accuracy.
- ✓ Cold light source, narrowband interference, with long lifetime up to 100,000 hours.
- ✓ Benchtop Type: Data transfer to PC via USB interface and optional bluetooth transmission.
- ✓ Portable Type: Advanced power management system can show the battery status in real time and be charged via USB port on PC or vehicle.