

NEW ADDITION

3510

DIGITAL PROBE SONICATOR

TECHNICAL SPECIFICATION

RATED POWER	: 250W
INPUT VOLTAGE	: 110V/220V-240V
INPUT FREQUENCY	: 50Hz-60Hz
OUTPUT POWER	: ≤250W
POWER AND AMPLITUDE ADJUST	: 0-100%
PACKING SIZE(CM)	: 32x46x42cm
MACHINE WEIGHT(KG)	: 7
SONOTRODE LENGTH	: 120mm
SONOTRODE DIAMETER	: 8mm
SONOTRODE FREQUENCY	: 20KHz
OPERATION PANEL DISPLAY	: Time setting Working data
WORKING MODE	: 1s-99 hours with pause function continuous working
GENERATOR PROTECTION	: Built-in circuit, Over loading, Over temperature, Antishort-circuit, Soft start
CABLE LENGTH	: 2M
ENVIRONMENT TEMP	: 0-40°C
RELATIVE HUMIDITY	: ≤85% T=20°C
MAX TEMPERATURE OF SONOTRODE	: 100°C
MAX PRESSURE	: 5Mpa
TREATMENT CAPACITY OF LIQUID	: ≤10L/H
BREAKER TYPE FOR BATCH	: 20ml-200ml



STANDARD ACCESSORIES

An Abs Soundproof Box,
A Stainless Steel Lifting Platform,
3 Fuse

