

MICROPROCESSOR COND-TDS-SAL METER

51



SALIENT FEATURES

- ✓ 128x64 dots Graphical LCD Display
- ✓ EC, TDS, Salinity & Temperature Measurements
- ✓ Auto Temperature Compensation
- ✓ Auto Ranging Facility
- ✓ Programmable Ref. Temp & Temp. Coeff in EC Mode
- ✓ 1000 Samples Storage Facility
- ✓ Printer Attachment Facility



TECHNICAL SPECIFICATIONS

PARAMETER	EC	TDS	SALINITY	TEMP.
✓ RANGE SEL.	Automatic	Automatic	Automatic	—
✓ RANGE	0-20, 0-200 μ S	0-2, 0-20, 0-200ppm	0-20, 0-200ppm	0-100°C
	0-2, 0-20, 0-200 μ S	0-20, 0-200 ppt	0-2, 0-20, 0-50ppt	
✓ ACCURACY	$\pm 0.5\%FS \pm 1$ Digit	$\pm 0.5\%FS \pm 1$ Digit	$\pm 1\% FS \pm 1$ Digit	$\pm 0.1^\circ C$
✓ RESOLUTION	0.01 μ S	0.01 ppm	0.01 ppm	0.1°C
✓ CELL CONST	Adjustable (0.05-9.99)	Adjustable (0.05-9.99)	Adjustable (0.05-9.99)	----
✓ TEMP. COMP	Auto/Manual 0-50°C	Auto/Manual 0-50°C	Auto/Manual 0-50°C	----
✓ TEMP. COEFF.	Adjustable (0.1 - 4.0%)	Adjustable (0.1 - 4.0%)	Adjustable (0.1 - 4.0%)	
✓ READOUT	128x64 dots Graphical LCD Display			
✓ KEY BOARD	5 Soft touch membrane type keys			
✓ PRINTER	USB Interface			
✓ STORAGE	Up to 1000 Samples			
✓ POWER	230V $\pm 10\%$ AC			
✓ ACCESSORIES	Cond./TDS/Salinity Cell, Temperature Probe, Electrode Stand, Mains Lead, Dust Cover, Instruction Manual			