

MTX - 1



Features:

- °C or °F Selection
- Circular Laser
- Auto Power Off (APO)
- Colour LED Display
- High Alarm Indicators

Technical Data :

Basic Functions	MTX1
Temperature Range	-50 ~ 550°C/-58~1022°F
Accuracy	-30°C-0°C(-22°F-32°F), ±3°C 0°C-55°C(-22°F-1022°F), ±(1.5%+2°C)
Distance Spot Ratio	12:1
Emissivity	adjustable 0.1~1.0
Resolution	0.1°C / 0.1°F

POWER

AAA 1.5V x 2

- Standard Accessories : Manual
- Dimension : 43(H) x 155(W) x 160(D)mm

MTX-2

LCD Alarm Indicator



Features:

- °C or °F Selection
- Circular Laser
- Auto Power Off (APO)
- Colour LCD Display
- LCD Alarm Indicator

Technical Data :

Basic Functions	MTX2
Temperature Range	-50°C ~ 580°C/ -58~1076°F
Accuracy	50~0°C / -58~32°F; ±4°C/7.2°F 0-550°C / 32~1022°F; ±2%(±2°C/3.6°F)
Distance Spot Ratio	13:1
Emissivity	adjustable 0.1~1.0
Resolution	0.1°C / 0.1°F

POWER

9V (6F22) X 1

- Standard Accessories : Soft Carrying Case Manual
- Dimension : 155(H) x 99(W) x 28(D)mm

MT4



Features:

- °C or °F Selection Circular
- Circular Laser
- Auto Power Off (APO)
- Data Hold Function
- Colour LCD Display

Technical Data :

Basic Functions	MT4
Temperature Range	-50 to 550°C / -58°F to 1022°F
Accuracy	-20°C to 0°C/-4°F to 32:4°C/7°F Above 0°C/32°F:±2%of reading±2°C/3.6°F
Distance Spot Ratio	12:1
Emissivity	adjustable 0.1 ~ 1.0
Spectral Response	8 ~ 14um
Resolution	0.1°C / 0.1°F

POWER

9V (6F22) X 1

- Standard Accessories : Soft Carrying Case, Manual
- Dimension : 132(H) x 55(W) x 168(D)mm

MT6



Features:

- °C or °F Selection Circular
- Circular Laser
- Auto Power Off (APO)
- Data Hold Function
- Colour LCD Display

Technical Data :

Basic Functions	MT6
Temperature Range	-50 ~ 750°C / -4~1382°F
Accuracy	± 2.0% of rdg+2°C digits
Distance Spot Ratio	12:1
Emissivity	adjustable 0.1~1.0
Spectral Response	(8~14)um
Resolution	0.1°C / 0.1°F

POWER

9V (6F22) X 1

- Standard Accessories : Soft Carrying Case, Manual
- Dimension : 132(H) x 55(W) x 168(D)mm

MT8

Features:

- °C or °F Selection
- Colour LCD
- Auto Power Off (APO)
- Circular Laser
- Data Hold Function



Technical Data :

Basic Functions	MT-8
Temperature Range	-50~800°C/-58~1472°F
Accuracy	±1.5%
Relative Humidity	0~99%RH
Accuracy	±5%RH
Distance Spot Ratio	12:1
Emissivity	adjustable 0.10~1.00
Spectral Response	8~14um
Resolution	0.1°C / 0.1°F

POWER

AAA 1.5V X 2

- Standard Accessories : Manual
- Dimension : 148(H) x 102(W) x 46 (D)mm

