

RYS- Series Microtome

RAYSCOPE

ERMA JAPAN TYPE ROTARY MICROTOME
UPGRAD-ABLE WITH DISPOSABLE BLADES

RYS-ARM I OB



MICROTOME AT GLANCE

CONVENIENTLY LOCATED FEED INDICATOR

ACCURATE SPECIMEN ADVANCE

CONVENIENT SPECIMEN HOLDER

SAFETY DEVICE

SMOOTH DRIVE WHEEL WITH LOCKING

STURDY, RIGID CONSTRUCTION FOR SHAKE PROOF CONSTRUCTION

MINIMAL MAINTENANCE

PROTECTIVE COVER FOR EASY CLEANING

ACCEPT ATTACHMENTS FOR DISPOSABLE BLADES

SPECIFICATIONS

RYS-ARM I OB

- ERMA MICROTOME IS A VERSATILE SECTIONING DEVICE SUITABLE FOR MEDICAL INSTITUTIONS, RESEARCH & PATHOLOGICAL LABORATORIES. THIS MICROTOME HAS SPECIAL APPLICATION FOR CUTTING THIN SECTIONS OF HISTOPATHOLOGICAL SPECIMENS AND ALSO CATER TO THE DEMANDS OF INDUSTRIES SUCH AS PLASTIC, LEATHERS, TEXTILES, RUBBER & FERTILIZER. IT IS IDEAL FOR THOSE WHO WANT TO AVAIL ADVANTAGES OF A ERMA MICROTOME AT A MODERATE COST. THE ENTIRE MECHANISM STANDS ON A HEAVY CAST IRON BASE ENSURING STABILITY AND RIGIDITY. ITS COMPOUND SLIDE WAYS OF CRITICAL TOLERANCES GUIDE THE SPECIMEN BLOCK. THE METAL HINGED COVER HOUSING PROTECTS THE INTERNAL MECHANISM AGAINST DUST AND PARAFFIN WASTE, IT CAN BE CONVENIENTLY OPENED FOR RESETTING, CLEANING AND LUBRICATING. THE MICROTOME IS DRIVEN BY A HANDLE WHICH CAN ALSO BE LOCKED. CUTTING SECTIONS ARE OBTAINED IN DIFFERENT THICKNESS BY MECHANICALLY OPERATED CRANK THROUGH A KNURLED KNOB IN FRONT OF THE INSTRUMENT.
- THE KNURLED KNOB IS GRADUATED IN MICRONS FOR FEED SETTING AND READY REFERENCE. A DETENT CLICK ACTION ENSURES POSITIVE ADJUSTMENTS IN ONE MICRON INCREMENT. THE KNIFE HOLDER UNIT IS EQUIPPED WITH A ROTATING KNIFE CLAMP TO ADJUST DESIRED ANGLES FOR BEST SECTIONING. IT HAS FORWARD AND BACKWARD MOVEMENTS TO ENSURE CONTACT OF SPECIMEN WITH THE KNIFE AND LATERAL MOVEMENT TO GET MAXIMUM USE OF KNIFE EDGE. SMOOTH & ACCURATE SPECIMEN MOVEMENT IS ACHIEVED WITH THE TIME PROVEN OPERATING PRINCIPLES OF THE FEED MECHANISM. TRAVEL IS ENTIRELY INDEPENDENT TO THE VERTICAL MOVEMENT OF THE SPECIMEN BLOCK. WHEN THE FEED LIMIT REACHES TO AN END POINT, IT DISENGAGES ITSELF. TO BRING THE FEED SCREW BACK, THE VICE IS PRESSED SLIGHTLY, AND THE MAIN GEAR WHEEL IS TURNED CLOCKWISE TILL THE SCREW REACHES ITS STARTING POSITION. ALL PARTS ARE FABRICATED FROM SELECTED ALLOYS AND THE MICROTOME KNIFE IS MANUFACTURED FROM FINE GRAIN STEEL TESTED TO MAINTAIN OPTIMUM SHARPNESS STRENGTH.
- FEED ADJUSTMENTS 1-25 μ M
- MINIMUM THICKNESS 1 μ M
- TOTAL FEED EXCURSIONS 28MM
- OVERALL DIMENSIONS 30X33X28CMS
- NET WEIGHT 25 KGS. APPROX.
- GROSS WEIGHT 35 KGS. APPROX.
- OBJECT HOLDERS (3 Nos.)
- KNIFE | 20MM IN A BOX HONING STONE.
- LUBRICATING OIL BOTTLE – 1 SET.
- DUST COVER – 1 PC.
- OPERATING MANUAL – 1 NO
- OPTIONAL ACCESSORIES:- RAZOR ATTACHMENTS, MICROTOME RAZORS/KNIVES, L-MOULDERS, OBJECT HOLDERS, HONING STONES, LEATHER STRAPS, MICRO ABRASIVES, RAZOR/KNIFE SHARPENERS AND RIBBON CONVEYER ETC.
- WARRANTY TWO YEARS AGAINST MANUFACTURING DEFECTS.
- CERTIFICATIONS ISO 9001, I 3485, US FDA AND CE CERTIFIED.

ERMA JAPAN TYPE ROTARY MICROTOME