Precision Table Top Scale













Standard Feature

- · Easy to read bright LED display.
- · High Resolution 15000-100000 stable count
- · High stability & better repeatability
- Respond Time 2 Second
- Multi Unite Available
- · Easy to Operate System
- Ultimate overload protection 150% of FS

| MODEL | CAPACITY | READABILITY | PAN SIZE (mm) |
|----------|----------|-------------|------------------------------|
| SES 3TH | 3kg | 0.1 g | 170 x 220 or 240 x 290 |
| SES 6TH | 6kg | 0.1 g | |
| SES 10TH | 10kg | 0.1 g | |
| SES 20TH | 20kg | 0.1 g | |
| SES 30TH | 30kg | 0.1 g | |
| SES 3T | 3kg | 0.5 g | |
| SES 6T | 6kg | 0.5 g | |
| SES 10T | 10kg | 0.5 g | |
| SES 20T | 20kg | 1 g | |
| SES 30T | 30kg | 1 g | |
| SES 50TH | 50kg | 1 g | |

- · Auto external calibration system
- · Inbuilt battery backup available for continue use
- · SS and ABS housing available
- · Environmentally protected load cell.
- · RS232, WiFi, Bluetooth facility, Printer (optional)
- · High / Low Indication
- Waterproof Body (optional)







STP01 - Thermal Data Printer

Standard Feature

- Admin Password Protected
- Unlimited Data Record Memory & Saving
- · Data Sending Facility by Mail, SMS
- Wifi system & Touch Screen Monitor Optional
- 21 CFR Compliance
- · GLP/GMP Compliance
- · Fast & Clear printing.
- Statistics printing facility available with date and time
- Name of company & code number can be printed.
- · Sum only & duplicate copy is possible.

- · Printing data available for long time.
- · No need of expensive ribbon cartridge.
- · No irritating sound of printing.
- Interface connectivity possible with all standard balances
- User friendly operation.
- Backlit LCD display.

SAFFRON Date Printer Lack Strain Date Printer

▶ Technical Specifications

| MODEL | STP 01 | |
|---|-------------------------------|--|
| Printing Method | Thermal direct line | |
| Paper | Thermal Paper | |
| Paper Size | 57 mm | |
| Printing Speed | 50 - 80 mm / sec | |
| Life of printing head | 50 cm | |
| Display | LED backlit | |
| Interface | RS 232C | |
| Statistics printing with date - time | Yes | |
| Sum and duplicate copy facility | Yes | |
| Company name code number | Yes | |
| Power supply | Input AC 110 - 250 (50/60) Hz | |
| Transmission parameter | 1200, 2400, 4800, 9600 baud | |
| Working temperature | 5 - 40°C | |
| Dimension (L x W x H) | 220 x 150 x 70 mm | |
| Id / n / min / max / diff / Ex / stdv / date / time | Yes | |

##